

# bizhub 300i

# Black & White A3 multifunctional









# **CUSTOMER BENEFITS**



Secure network integration, data encryption, hard drive overwrite, and advanced user authentication



## **Productivity**

Reliability, high-speed scanning and printing, combined with powerful finishing functions



### Sustainability

Numerous eco features reduce energy consumption and costs



#### Intuitive operability

Operate the bizhub like a smartphone or tablet with fully customised user interface



## **Application ecosystem**

Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio




**Services**Efficient printer fleet management, including automatic con-sumables delivery, pro-active maintenance and remote setup


# **OPTIONS**




Antivirus LK-116 FOIP activation LK-117













Keyboard holder

Air cleaning unit

# FINISHING FUNCTIONALITIES



























stapling stapling

punching

punching

Duplex

Half-fold mixplex/

insertion. report

Letter-fold

Booklet

Offset sorting printing

Stapling (offline)

# **DESCRIPTION**

ENHANCED FEATURES	
LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-114 Serverless pull printing	Secure and Follow Me printing solution requiring no server
	application
LK-115v2 Trusted Platform Module	Trusted Platform Module for protection of data encryption and
	decryption
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all
	incoming and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit
CONNECTIVITY	
CONNECTIVITY  EK-608 USB I/F kit	USB keyboard connection
	USB keyboard connection Installation kit for ID card reader
EK-608 USB I/F kit	
EK-608 USB I/F kit MK-735 Mount kit	Installation kit for ID card reader
EK-608 USB I/F kit MK-735 Mount kit ID card reader	Installation kit for ID card reader Various ID card technologies
EK-608 USB I/F kit MK-735 Mount kit ID card reader AU-102 Biometric authentication	Installation kit for ID card reader Various ID card technologies Finger vein scanner
EK-608 USB I/F kit MK-735 Mount kit ID card reader AU-102 Biometric authentication FK-514 Fax board	Installation kit for ID card reader Various ID card technologies Finger vein scanner Super G3 fax, digital fax functionality
EK-608 USB I/F kit MK-735 Mount kit ID card reader AU-102 Biometric authentication FK-514 Fax board EK-609 USB I/F kit	Installation kit for ID card reader  Various ID card technologies  Finger vein scanner  Super G3 fax, digital fax functionality  USB keyboard connection; Bluetooth
EK-608 USB I/F kit MK-735 Mount kit ID card reader AU-102 Biometric authentication FK-514 Fax board EK-609 USB I/F kit	Installation kit for ID card reader  Various ID card technologies  Finger vein scanner  Super G3 fax, digital fax functionality  USB keyboard connection; Bluetooth
EK-608 USB I/F kit MK-735 Mount kit ID card reader AU-102 Biometric authentication FK-514 Fax board EK-609 USB I/F kit UK-221 Wireless LAN	Installation kit for ID card reader  Various ID card technologies  Finger vein scanner  Super G3 fax, digital fax functionality  USB keyboard connection; Bluetooth

OTHERS	
OC-511 Original Cover	Cover instead of ADF
WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
CU-102 Air cleaning unit	Improving indoor air quality by reduced emission
KH-102 Keyboard holder	To place USB keyboard
MEDIA INPUT	
IM-102 Intelligent media sensor	Autodetects paper weight and type
PC-116 1x Universal tray	500 sheets, A5–A3, 52–256 g/m <sup>2</sup>
PC-216 2x Universal tray	2x 500 sheets, A5–A3, 52–256 g/m <sup>2</sup>
PC-416 Large capacity tray	2,500 sheets, A4, 52–256 g/m <sup>2</sup>
PC-417 Large capacity tray	1,500 + 1,000 sheets, A5-A4, 52-256 g/m <sup>2</sup>
LU-302 Large capacity tray	3,000 sheets, A4, 52–256 g/m <sup>2</sup>
BT-C1e Banner tray	Multipage banner feeding
DK-516x Copier desk	Provides storage space for print media and other materials
MEDIA OUTPUT	
FS-539 Staple finisher	50 sheets stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50 sheets stapling; 20 sheets booklet finisher;
	2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/4 hole punching; autoswitching
RU-513 Relay unit	For FS-539/SD installation
JS-506 Job separator	Separation of fax output; etc.
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
PK-519 Punch kit for FS-533	2/4 hole punching, autoswitching

# **TECHNICAL SPECIFICATIONS**

System speed A4	Up to 30 ppm
System speed A3	Up to 15 ppm
Autoduplex speed A4	Up to 30 ppm
1st page out time A4	5.0 sec.
Warm-up time	Approx. 11 sec. <sup>1</sup>
Imaging technology	Laser
Toner technology	Simitri® HD polymerised toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S)
Automatic document feeder	Up to 100 originals; A6-A3; 35-163 g/m²;
(optional)	RADF or Dualscan ADF available
ADF double feed detection	Standard (with dualscan ADF)
Printable paper size	A6-SRA3; banner paper max. 1,200 x 297 mm,
	customized paper sizes
Printable paper weight	52-300 g/m <sup>2</sup>
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500; A6–A3; custom sizes; 52–256 g/m <sup>2</sup>
	1x 500; A5-SRA3; custom sizes; 52-256 g/m <sup>2</sup>
Paper tray input (optional)	1x 500 sheets; A5–A3; 52–256 g/m <sup>2</sup>
	2x 500 sheets; A5–A3; 52–256 g/m <sup>2</sup>
	1x 2,500 sheets; A4; 52–256 g/m <sup>2</sup>
	1x 1,500 + 1x 1,000 sheets; A5-A3; 52-256 g/m <sup>2</sup>
Large capacity tray (optional)	1x 3,000; A4; 52–256 g/m <sup>2</sup>
Manual bypass	150 sheets; A6–SRA3; custom sizes, banner; 60–300 g/m <sup>2</sup>

SYS	I EM SI	PECIFICA	HONS

Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet
Automatic duplexing	A6-SRA3; 52-256 g/m <sup>2</sup>
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 50 sheets or 48 sheets + 2 cover sheets (up to 209 g/m²)
Stapling output capacity	Max. 100 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 30 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 209 g/m²)
Booklet output capacity	Max. 20 booklets; unlimited (without tray)
Duty cycle (monthly)	Rec. 25,000 pages; Max. <sup>2</sup> 150,000 pages
Toner lifetime	Black up to 25,000 pages
Imaging unit lifetime	Black up to 245,000/1,000,000 pages (drum/developer)
Power consumption	220-240 V / 50/60 Hz; Less than 1.58 kW
System dimension (W x D x H)	615 x 688 x 779 mm (without options)
System weight	Approx. 76.0 kg (without options)

## PRINTER SPECIFICATIONS

FRINTER SFECII ICATIONS	
Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2; Windows Server
	2016; Windows Server 2019; Macintosh OS X 10.10 or later; Linux
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android);
	AirPrint (iOS); Mopria (Android)
	optional: WiFi Direct

### SCANNER SPECIFICATIONS

Scan speed	Up to 100/100 ipm in simplex (mono/colour)
	Up to 200/200 ipm in duplex (mono/colour)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS;
	Compact XPS; PPTX
	optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

### **COPIER SPECIFICATIONS**

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	Max. A3
Magnification	25-400% in 0.1% steps; Auto-zooming

### FAX SPECIFCIATION

Fax standard	Super G3 (optional)
Fax transmission	Analogue; i-Fax; Colour i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

# LICED BOY CDECIFICATIONS

OSEK BOX SPECIFICATION	5
Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling

### SYSTEM FEATURES

Security	ISO 15408 HCD-PP Common Criteria (in evalutation);
	IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	Hard drive overwrite; Hard drive data encryption (AES 256);
	Confidential fax; Print user data encryption
	optional: Antivirus realtime scanning (Bitdefender®);
	Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	optional: Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator;
	Web Connection; Print Status Notifier; Driver Packaging Utility;
	Log Management Utility

<sup>&</sup>lt;sup>1</sup> Warm-up time may vary depending on the operating environment and usage

- All specifications refer to A4-size paper of 80 g/m² quality.
   The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

  - The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
- particular page size (6% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



# Speak to us

T: 0800 046 1332

E: info@insightsystems.co.uk W:www.insightsystems.co.uk



























 $<sup>^{\</sup>mathrm{2}}$  If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed